

SOLVLVGP Datasheet

2-Way, Internally Piloted Normally Closed, 1/2" - 2" NPT







120VAC, 24VAC or 24VDC Power Input



UL Listed



Normally Closed Safety Shutoff



1/2" to 2" NPT Available For This Model Various Other Sizes Also Available

Product Overview

CGS water solenoid valves are normally closed (N/C) and constructed with a durable brass body, two-way inlet and outlet ports.

Sizes Available

120VAC Models

Valve Size " (inch) NPT	CGS Part Number
1/2"	SOLVLVGP12
3/4"	SOLVLVGP34
1"	SOLVLVGP1
1+1/4"	SOLVLVGP114
1+1/2"	SOLVLVGP112
2"	SOLVLVGP2

24VDC & 24VAC Models

Valve Size " (inch) NPT	CGS Part Number
1/2"	SOLVLVGP12-24VDC or AC
3/4"	SOLVLVGP34-24VDC or AC
1"	SOLVLVGP1-24VDC or AC
1+1/4"	SOLVLVGP114-24VDC or AC
1+1/2"	SOLVLVGP112-24VDC or AC
2"	SOLVLVGP2-24VDC or AC

Electrical Specifications

Voltage	120VAC / 24VAC	Voltage	24VDC
Frequency Hz	50/60	Frequency Hz	DC
Power (VA)	20	Power (W)	17 W
Rating	Nema 4	Rating	Nema 4
Coil Type	D	Coil Type	D
Coil Class	F	Coil Class	F

Materials of Construction

Body	Brass
Armature Tube	Stainless Steel 300
Fixed Core	Stainless Steel 400
Plunger	Stainless Steel 400
Spring	Stainless Steel 300
Shading Ring	Copper
Orifice	Brass



Technical Specifications

120VAC Models

Pipe		Flow					External Dimensions				
Size	Orifice	Factor	Pressure	Temp.			Length x Width x Height		Connector		Sealing
(Inch)	(Inch)	(CV)	(PSI)	Range	Voltage	Rating	(Inches)	Model	Supplied	Medium Examples	Material
1/2"	1/2"	4.5	0.5-230	32-266°F	120VAC	20	2.59 x 1.89 x 4.21	SOLVLVGP12	Wire Connector	Water Non-Potable & Air	EPDM
3/4"	3/4"	7.6	0.5-230	32-266°F	120VAC	20	2.95 x 2.28 x 4.40	SOLVLVGP34	Wire Connector	Water Non-Potable & Air	EPDM
411	4.0	40	0.5.000	00 00005	4000/40		0.70 0.70 5.40	0011/11/004			FDDM
1"	1"	12	0.5-230	32-266°F	120VAC	20	3.78 x 2.76 x 5.16	SOLVLVGP1	Wire Connector	Water Non-Potable & Air	EPDM
1 1/4"	1 1/4"	22	0.5-230	32-266°F	1201/40	20	5.16 x 3.78 x 5.75	SOLVLVGP114	Wire Connector	Water Non-Potable & Air	EDDM
1 1/4	1 1/4	22	0.5-230	32-200 F	120VAC	20	5.16 X 3.76 X 5.75	SULVLVGP114	vvire Connector	vvaler Nori-Potable & Air	EPDIM
1 1/2"	1 1/2"	30	0.5-230	32-266°F	120\/AC	20	5.16 x 3.78 x 5.75	SOLVLVGP112	Wire Connector	Water Non-Potable & Air	EDDM
1 1/2	1 1/2	30	0.5-250	32-200 T	IZUVAO	20	3.10 x 3.70 x 3.73	SOLVEVOI 112	vviie Connector	Water North Stable & All	LI DIW
2"	2"	48	0.5-230	32-266°F	120VAC	20	6.50 x 4.72 x 6.57	SOLVLVGP2	Wire Connector	Water Non-Potable & Air	EPDM

24VAC Models

Pipe	Orifice	Flow	Pressure	Temp.		VA	External Dimensions		Connector		Sealing
Size	(Inch)	Factor	(PSI)	Range	Voltage	Rating	Length x Width x Height	Model	Supplied	Medium Examples	Material
1/2"	1/2"	4.5	0.5-190	32-266°F	24VAC	20	2.59 x 1.89 x 4.21	SOLVLVGP12-24VAC	Wire Connector	Water Non-Potable & Air	EPDM
3/4"	3/4"	7.6	0.5-190	32-266°F	24VAC	20	2.95 x 2.28 x 4.40	SOLVLVGP34-24VAC	Wire Connector	Water Non-Potable & Air	EPDM
1"	1"	12	0.5-190	32-266°F	24VAC	20	3.78 x 2.76 x 5.16	SOLVLVGP1-24VAC	Wire Connector	Water Non-Potable & Air	EPDM
1 1/4"	1 1/4"	22	0.5-115	32-266°F	24VAC	20	5.16 x 3.78 x 5.75	SOLVLVGP114-24VAC	Wire Connector	Water Non-Potable & Air	EPDM
1 1/2"	1 1/2"	30	0.5-115	32-266°F	24VAC	20	5.16 x 3.78 x 5.75	SOLVLVGP112-24VAC	Wire Connector	Water Non-Potable & Air	EPDM
2"	2"	48	0.5-115	32-266°F	24VAC	20	6.50 x 4.72 x 6.57	SOLVLVGP2-24VAC	Wire Connector	Water Non-Potable & Air	EPDM

24VDC Models

Pipe	Orifice	Flow	Pressure	Temp.		(W)	External Dimensions		Connector		Sealing
Size	(Inch)	Factor	(PSI)	Range	Voltage	Rating	Length x Width x Height	Model	Supplied	Medium Examples	Material
1/2"	1/2"	4.5	0.5-190	32-266°F	24VDC	17	2.59 x 1.89 x 4.21	SOLVLVGP12-24VDC	Wire Connector	Water Non-Potable & Air	EPDM
3/4"	3/4"	7.6	0.5-190	32-266°F	24VDC	17	2.95 x 2.28 x 4.40	SOLVLVGP34-24VDC	Wire Connector	Water Non-Potable & Air	EPDM
1"	1"	12	0.5-190	32-266°F	24VDC	17	3.78 x 2.76 x 5.16	SOLVLVGP1-24VDC	Wire Connector	Water Non-Potable & Air	EPDM
1 1/4"	1 1/4"	22	0.5-115	32-266°F	24VDC	17	5.16 x 3.78 x 5.75	SOLVLVGP114-24VDC	Wire Connector	Water Non-Potable & Air	EPDM
1 1/2"	1 1/2"	30	0.5-115	32-266°F	24VDC	17	5.16 x 3.78 x 5.75	SOLVLVGP112-24VDC	Wire Connector	Water Non-Potable & Air	EPDM
2"	2"	48	0.5-115	32-266°F	24VDC	17	6.50 x 4.72 x 6.57	SOLVLVGP2-24VDC	Wire Connector	Water Non-Potable & Air	EPDM

Find out more Canadian Gas Safety Inc

www.canadiangassafety.com

Head office: 150 King Street West Suite 200,

Toronto, ON M5H 1J9 Tel: (647) 577-1500

Email: info@canadiangassafety.com

