

CGSPGT7M Datasheet

Digital In-Wall Timer With Lockable Metal Cover



7.88" (H) x 5.13" (W) x 3.44" (D)

Ratings

Enclosure Options: Standard: Type 1 Gray Painted Steel

Knockouts: Combination ½" & ¾" knockouts Bottom:

2, Left: 1, Right: 1, Back: 1

Frequency: 120, 208, 240, 277 VAC 50/60 Hz

Operating Temperature: -40°F to 155°F (-40°C to 68°C)

N.O. Contact Ratings: Resistive: 30 Amps @ 120/240 VAC

Resistive: 20 Amps @ 28 VDC Inductive: 30 Amps @ 120/240 VAC




Product Overview

The CGSPGT7M 7-Day Electronic Time Switches feature independent 7-day programming to provide flexibility for applications. These time switches provide dependable and uncomplicated performance, plus to-the-minute programming for a accurate load control and reduced energy costs. Up to 28 set points or events can be pre-set to automatically repeat. The program can be disabled at any time by placing the time switch in the Manual operating mode. Control buttons provide manual control of each circuit independently regardless of the operating mode. Each time switch is housed in a lockable enclosure to protect against vandalism and unauthorized tampering.

Key Features

- ✓ Program can be repeated on a weekly basis
- ✓ Multi-volt operation from 120-277 VAC, 50/60 Hz
- ✓ To-the-minute programming for accurate load control and reduced energy costs
- Up to 28 setpoints
- ✓ Automatic Daylight Saving Time (DST) ON/OFF adjustment (factory enabled)
- √ Non-volatile EEPROM memory protects programming indefinitely
- Temporary override or permanent manual override available via control buttons
- 2-circuit models are field (jumper) configurable for: 2

independent outputs, DPST output, or 1 channel ON pulse/OFF pulse output



Find out more

Canadian Gas Safety Inc

www.canadiangassafety.com

Head office: 150 King Street West Suite 200,

Toronto, ON M5H 1J9 Tel: (647) 577-1500

Email: info@canadiangassafety.com

