

CGSPBTW Datasheet

Emergency Shut Off Push Button With Twist-Reset





Product Overview

The CGSPBTW, multipurpose push button to be used for a wide range of applications, most commonly used with the CGS Merlin range of gas safety systems.

The CGSPBTW is a remote mounted push-to-break contact, twist-to-reset emergency push button. It has a plastic wall mounting box, screw fix to flat surface. Connect electrical supply through single pole switch block via screw terminals.

Key Features

- ✓ Protects against vandalism, accidental damage, dust and grime
- ✓ Indoor use only
- ✓ Twist Release Reset

Construction

- ✓ UL Listed to U.S. and Canadian safety standards.
- ✓ Contacts: 10a 500v max single pole
- √ Temperature range: 25°c to + 70°c protection: IP40

Installation

- 1. Separate switch base and top
- 2. Mount using the base as a template for holes
- 3. Knock out hole at top or bottom of base to allow cable entry
- 4. Feed cable through a cable gland and hole
- 5. Make necessary electrical connections
- 6. Replace switch top

Note: Key is captive on key reset models when the switch is in the unlatched position $% \left(1\right) =\left(1\right) \left(1\right) \left($

Dimensions



3.15" (H) x 2.87" (W) x 1.97" (D)

Find out more

Canadian Gas Safety Inc

www.canadiangassafety.com

Head office: 150 King Street West Suite 200,

Toronto, ON M5H 1J9 Tel: (647) 577-1500

Email: info@canadiangassafety.com

