




Features

- 24VDC Power Input
- Traffic Light Indicator Display Changes Color Dependent On Gas Levels
- Modern & Compact Design
- Plug & Play Installation
- Standalone Detector or Used with a CGS Controller
- Alarm Relay Dry Contact
- In-Built Audible Alarm
- BMS/BAS Communications

Product Overview

The iS range of CGS detectors work in combination with the CGS Merlin range of Gas Detection panels and Utility Controllers or can be used as a standalone detector. The CGSLPGiS features an electrochemical sensor for industrial and commercial indoor applications. Compact, modern, digital design makes the units aesthetically pleasing and easy to install.

Circuit board Diagram




Popular Applications



Technical Specifications

General							
Model:		Detector i-S					
Target Gas		LPG					
Size: (H x W x D)		5.95 x 4.37 x 1.97" (151 x 111 x 50mm)					
Housing Material:		ABS PA765. Flame Retardant UL 94V-1					
Mounting:		Safe Zone - Indoor use - Wall Mounted					
Weight:		212g					
User Interface							
Display:		1.8" TFT					
Screen Brightness:		Non-Adjustable					
Visual Indicators:		Gas Level (Green: Normal; Yellow: Pre-Alarm; Red: Alarm) 0-10V Output: Relay Output					
Audible Alarm:		>65dB @ 3.28ft (1m). Quiet conditions.					
Language:		English					
Power Supply							
Max. Power Consumption:		1.8W					
Power Rating:		12-24V AC or DC					
Relays							
Volt Free BMS relay outputs:		1A switching current (resistive load) @ 24V AC/DC					
Environmental							
Ingress Protection (IP):		Not Formally Evaluated					
Operating:		-10 ~ 50°C / 14 ~ 122°F / 20 ~ 90% RH (non-condensing)					
Storage:		0 ~ 50°C / 32 ~ 122°F / 30 - 80% RH (no condensation)					
Altitude Rating:		2000m					
Wiring							
Typical		Min. 2.5mm2 / 75°C min / Tinned copper.					
Approvals							
Electrical Safety		BS EN 61010-1:2010 +A1:2019.					
Electromagnetic Compatibility		BS EN 50270.					
Sensor Specification							
Factory Calibration Conditions		25° ± 5°C - 77° ± 41°F (40-70% RH)					
Sensor Type		Semiconductor					
Gas Sensor	Measuring Range (%LEL)	Calibration Gas	Response (T90)	Recovery (T10)	Alarm: 1 (Pre alarm warning)	Alarm: 2	*EOL (Years)
Liquid Petroleum Gas (LPG)	0-10%	10% LEL	<30s	<30s	▲8%LEL	▲10%LEL	10



Areas of coverage

Consider the coverage required and function of the area. Emphasis should be placed on airflow patterns and correct placement, not perceived detecting ranges.

The CGSLPGiS monitor should be installed approximately 1ft from the ground level.