



Features

- Protects against vandalism, accidental damage, dust and grime
- For indoor and outdoor use
- Keyed release reset
- ADA Compliant
- Various colors, text & design types available upon request

Product Overview

The CGS-ESOKLWMA, multipurpose push button to be used for a wide range of applications with the CGS Merlin range of gas safety systems.

The CGS-ESOKLWMA is a keyed reset, flush mounted button and comes with a clear protective cover to avoid accidental activations. It also has an audible alarm if the protective shield is opened.

Construction

- Station housing molded of tough polycarbonate
- UL listed to U.S. and Canadian safety standards
- 5VA flammability rating on back plate and spacer
- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C)
- Polycarbonate complies with FDA regulations for food contact applications

Specification

- 1/2 HP, 6 amps @ 30 VDC.
- Switch rating 10 amps @ 240 VAC resistive and has a timer range:
- 2 - 60 seconds ($\pm 15\%$).
- Temperature range of button 15° to 120°F (-9° to +49°C).
- Two (2) Form "C" contacts, DPDT, rated 10 amps @ 125/250 VAC, 1 N.O. and 1 N.C. contact.

CGSESOKLWMA Emergency Power Off Push Button With Keyed-Reset, Weatherproof Cover & Audible Alarm

Dimensions

